# **SAFETY DATA SHEET**

Version 4.15 Revision Date 06/02/2016 Print Date 02/17/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Sodium fluoride

Product Number : S6776
Brand : Sigma

Index-No. : 009-004-00-7

CAS-No. : 7681-49-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

### 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 2), H300 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Acute aquatic toxicity (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H300 Fatal if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H402 Harmful to aquatic life.

Precautionary statement(s)

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.

Sigma - S6776 Page 1 of 9

P280 Wear protective gloves.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse

mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Contact with acids liberates very toxic gas.

Strong hydrogen fluoride-releaser

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Formula : FNa

 Molecular weight
 : 41.99 g/mol

 CAS-No.
 : 7681-49-4

 EC-No.
 : 231-667-8

 Index-No.
 : 009-004-00-7

**Hazardous components** 

Component	Classification	Concentration
Sodium fluoride		
	Acute Tox. 3; Skin Irrit. 2; Eye	<= 100 %
	Irrit. 2A; Aquatic Acute 3;	
	H301, H315, H319, H402	

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

## 4.1 Description of first aid measures

### General advice

Hydrofluoric (HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24 hours depending on the concentration of HF. After decontamination with water, further damage can occur due to penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases. More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician is experienced in this technique, due to the potential for tissue injury from increased pressure. Absorption can readily occur through the subungual areas and should be considered when undergoing decontamination. Prevention of absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and cardiac arrhythmias should be monitored for, since they can occur after exposure. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician. First treatment with calcium gluconate paste.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Sigma - S6776 Page 2 of 9

## 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## 5. FIREFIGHTING MEASURES

## 5.1 Extinguishing media

## Suitable extinguishing media

Dry powder

## 5.2 Special hazards arising from the substance or mixture

No data available

## 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

## 5.4 Further information

No data available

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

# 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Do not flush with water. Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Never allow product to get in contact with water during storage. Do not store near acids.

Moisture sensitive. Keep in a dry place. Do not store in glass

Storage class (TRGS 510): Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Components with workplace control parameters

Sigma - S6776 Page 3 of 9

Sodium fluoride  7681-49-4  TWA  2.500000  mg/m3  (OSHA) - Table 2-1 Limits for Air Contaminants  TWA  2.500000  Mg/m3  (OSHA) - Table 2-1 Limits for Air Contaminants  TWA  2.500000  USA. Occupational Exposure Limits  (OSHA) - Table 2-2  TWA  2.500000  USA. NIOSH Recommended mg/m3  Exposure Limits  TWA  2.500000  USA. NIOSH Recommended (OSHA) - Table 2-1 Limits for Air Contaminants  Remarks  CAS number varies with compound  TWA  2.500000  USA. Occupational Exposure Limits  (OSHA) - Table 2-1 Limits for Air Contaminants  Remarks  CAS number varies with compound  TWA  2.500000  USA. Occupational Exposure Limits  (OSHA) - Table 2-1  Exposure Limits  (OSHA) - Table 2-2  Z37.28-1969  TWA  2.500000  USA. ACGIH Threshold Limit Values  (See BE\(\text{E}\text{V}\text{S ecction}\)  Not classifiable as a human carcinogen  varies  TWA  2.500000  USA. ACGIH Threshold Limit Values  (See BE\(\text{V}\text{S ecction}\)  Not classifiable as a human carcinogen  varies  TWA  2.500000  USA. ACGIH Threshold Limit Values  (See BE\(\text{V}\text{S ecction}\)  Not classifiable as a human carcinogen  varies  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values  (See BE\(\text{V}\text{S ecction}\)  Not classifiable as a human carcinogen  varies  TWA  2.5 mg/m3  USA. NOLSH Recommended  Exposure Limits  (OSHA) - Table Z-1 Limits for Air  Contaminants - 1910.1000  TWA  2.5 mg/m3  USA. NOLOSH Recommended  Exposure Limits  USA. NOLOSH Recommended  Exposure Limits  (OSHA) - Table Z-1 Limits for Air  Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values  (ILV)  Bone damage  Fluorosis  Substances for which there is a Biological Exposure limits  (OSHA) - Table Z-1 Limits for Air  Contaminants  (ILV)  Bone damage  Fluorosis  Substances for which there is a Biological Exposure limits  (OSHA) - Table Z-1 Limits for Air  Contaminants  (ILV)  Bone damage  Fluorosis  Substances for which there is a Biological Exposure limits  (ILV)  Bone damage  Fluorosis	Component	CAS-No.	Value	Control	Basis	
Sodium fluoride   7681-49-4   TWA		0.10.10.	7 3.1.0.0			
mg/m3	Sodium fluoride	7681-49-4	TWA		USA, Occupational Exposure Limits	
TWA 2.500000 USA. Occupational Exposure Limits mg/m3 (OSHA) - Table Z-2  TWA 2.500000 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits mg/m3 (OSHA) - Table Z-2  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis  Substances for which there is a Biological Exposure Index or Indices (see BEI® section)  Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis  Substances for which there is a Biological Exposure Index or Indices (see BEI® section)  Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. OCcupational Exposure Limits  (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis  Substances for which there is a Biological Exposure Index or Indices (see BEI® section)  Not classifiable as a human carcinogen varies  CAS number varies with compound						
TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-2  TWA 2.500000 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-2 Limits for Air Contaminants  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (OSHA) - Table Z-2  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (SHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  CAI California permissible exposure limits for chemical contaminants						
mg/m3			TWA	2 500000		
TWA 2.500000 USA. NIOSH Recommended Exposure Limits TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-2  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  CAS formal Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies			1,			
May			TWA			
TWA 2.50000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits mg/m3 (OSHA) - Table Z-2  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. Oscupational Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. Oscupational Exposure Limits for Air Contaminants - 1910.1004  TWA 2.5 mg/m3 USA. Occupational Exposure Limits  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (OSHA) - Table 2-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants			,			
Remarks			TWA			
Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-2  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants			1			
Remarks CAS number varies with compound  TWA 2.500000 USA. Occupational Exposure Limits (OSHA) - Table Z-2  Z37.28-1969  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values (fLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Oscupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants					1 '	
TWA   2.500000   USA. Occupational Exposure Limits mg/m3 (OSHA) - Table Z-2    237.28-1969   TWA   2.500000   USA. ACGIH Threshold Limit Values mg/m3 (TLV)    Bone damage Fluorosis   Substances for which there is a Biological Exposure Index or Indices (see BEI® section)   Not classifiable as a human carcinogen varies    TWA   2.500000   USA. ACGIH Threshold Limit Values mg/m3 (TLV)    Bone damage Fluorosis   Substances for which there is a Biological Exposure Index or Indices (see BEI® section)   Not classifiable as a human carcinogen varies    TWA   2.5 mg/m3   USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000    TWA   2.5 mg/m3   USA. NIOSH Recommended Exposure Limits    TWA   2.5 mg/m3   USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000    TWA   2.5 mg/m3   USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants    CAS number varies with compound   TWA   2.5 mg/m3   USA. ACGIH Threshold Limit Values (TLV)    Bone damage   Fluorosis   Substances for which there is a Biological Exposure Index or Indices (see BEI® section)   Not classifiable as a human carcinogen varies    PEL   2.5 mg/m3   California permissible exposure limits for chemical contaminants		Remarks	CAS numbe	er varies with comp		
Mg/m3   (OSHA) - Table Z-2						
TWA 2.500000 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants						
TWA 2.500000			Z37.28-1969	<u> </u>	(00.00)	
Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants					USA, ACGIH Threshold Limit Values	
Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA   2.500000   USA. ACGIH Threshold Limit Values mg/m3   (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA   2.5 mg/m3   USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA   2.5 mg/m3   USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000  TWA   2.5 mg/m3   USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA   2.5 mg/m3   USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL   2.5 mg/m3   California permissible exposure limits for chemical contaminants			' ' ' ' '			
Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA  2.500000  WSA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA  2.5 mg/m3  USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA  2.5 mg/m3  USA. NIOSH Recommended Exposure Limits  TWA  2.5 mg/m3  USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			Bone damag		(124)	
Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.500000 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants				jC		
(see BEI® section) Not classifiable as a human carcinogen varies  TWA   2.500000   USA. ACGIH Threshold Limit Values mg/m3   (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA   2.5 mg/m3   USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA   2.5 mg/m3   USA. NIOSH Recommended Exposure Limits   USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA   2.5 mg/m3   USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL   2.5 mg/m3   California permissible exposure limits for chemical contaminants				for which there is a	Biological Exposure Index or Indices	
Not classifiable as a human carcinogen varies  TWA 2.50000					a biological Exposure mack of maloes	
TWA 2.500000 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants					rcinogen	
TWA 2.500000 mg/m3 USA. ACGIH Threshold Limit Values mg/m3 (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants						
mg/m3   (TLV)				2 500000	USA ACGIH Threshold Limit Values	
Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA  2.5 mg/m3  USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA  2.5 mg/m3  USA. NIOSH Recommended Exposure Limits  USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			,			
Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA  2.5 mg/m3  USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA  2.5 mg/m3  USA. NIOSH Recommended Exposure Limits  TWA  2.5 mg/m3  USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			Bone damad		()	
Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  TWA 2.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants			-	, •		
(see BEI® section) Not classifiable as a human carcinogen varies  TWA  2.5 mg/m3  USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  USA. NIOSH Recommended Exposure Limits  TWA  2.5 mg/m3  USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants				for which there is a	a Biological Exposure Index or Indices	
Not classifiable as a human carcinogen varies  TWA  2.5 mg/m3  USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA  2.5 mg/m3  USA. NIOSH Recommended Exposure Limits  USA. Occupational Exposure Limits  (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants					9 1 9 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
varies  TWA  2.5 mg/m3  USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  TWA  2.5 mg/m3  USA. NIOSH Recommended Exposure Limits  USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants						
Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants					•	
Air Contaminants - 1910.1000  TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits  TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants			TWA	2.5 mg/m3	USA. OSHA - TABLE Z-1 Limits for	
TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section)  Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants					Air Contaminants - 1910.1000	
TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section)  Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants			TWA	2.5 mg/m3	USA, NIOSH Recommended	
TWA 2.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants						
CAS number varies with compound  TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			TWA	2.5 mg/m3		
CAS number varies with compound  TWA 2.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants						
TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants						
TWA  2.5 mg/m3  USA. ACGIH Threshold Limit Values (TLV)  Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			CAS numbe			
Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants						
Bone damage Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants						
Fluorosis Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			Bone damag	je		
Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants						
(see BEI® section) Not classifiable as a human carcinogen varies  PEL  2.5 mg/m3  California permissible exposure limits for chemical contaminants			Substances for which there is a Biological Exposure Index or Indice (see BEI® section)			
Not classifiable as a human carcinogen varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants						
varies  PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants						
limits for chemical contaminants						
			PEL	2.5 mg/m3	California permissible exposure	
(Title 8, Article 107)				_		
					(Title 8, Article 107)	

**Biological occupational exposure limits** 

Biological cocapational expecute initio					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Sodium fluoride	7681-49-4	Fluoride	2 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	Prior to shift (1	6 hours afte	r exposure ceases)	

Sigma - S6776 Page 4 of 9

Fluoride	3 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
End of shift (As soon as possible after exposure ceases)			

## 8.2 Exposure controls

## **Appropriate engineering controls**

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

## Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

a) Appearance Form: powder

Colour: white

b) Odourc) Odour Thresholdd) pHNo data availableNo data available

e) Melting point/freezing Melting point/range: 993 °C (1,819 °F)

point

Sigma - S6776 Page 5 of 9

f)	Initial boiling point and boiling range	No data available
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	1.9 hPa (1.4 mmH
I)	Vapour density	No data available

Hg) m) Relative density 2.780 g/cm3 n) Water solubility No data available o) Partition coefficient: n-No data available

octanol/water

Auto-ignition temperature

No data available

Decomposition temperature

No data available

Viscosity No data available No data available s) Explosive properties Oxidizing properties No data available

#### 9.2 Other safety information

No data available

# 10. STABILITY AND REACTIVITY

#### Reactivity 10.1

No data available

## 10.2 Chemical stability

Stable under recommended storage conditions.

#### Possibility of hazardous reactions 10.3

Contact with acids liberates very toxic gas.

#### 10.4 Conditions to avoid

Exposure to moisture

Reacts dangerously with glass.

# 10.5 Incompatible materials

Strong acidsglass

#### 10.6 **Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Hydrogen fluoride, Sodium oxides Other decomposition products - Gaseous hydrogen fluoride (HF).

In the event of fire: see section 5

## 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

## **Acute toxicity**

LD50 Oral - Rat - female - 148.5 mg/kg

Inhalation: No data available Dermal: No data available

Sigma - S6776 Page 6 of 9 LD50 Intravenous - Rat - 26 mg/kg

Remarks: Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

### Skin corrosion/irritation

Irritating to skin.

## Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h Remarks: Moderate eye irritation

## Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

## Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

## Reproductive toxicity

No data available

No data available

## Specific target organ toxicity - single exposure

No data available

### Specific target organ toxicity - repeated exposure

No data available

## **Aspiration hazard**

No data available

### **Additional Information**

RTECS: WB0350000

Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia.

prolonged or repeated exposure can cause:, Damage to the lungs.

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

## 12. ECOLOGICAL INFORMATION

# 12.1 Toxicity

Sigma - S6776

Toxicity to fish mortality NOEC - Cyprinodon variegatus (sheepshead minnow) - 500 mg/l - 96

EC50 - Daphnia magna (Water flea) - 98 mg/l - 48 h

h

LC50 - Oncorhynchus mykiss (rainbow trout) - 200 mg/l - 96 h

Toxicity to daphnia and

other aquatic invertebrates

Page 7 of 9

# 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

Bioaccumulation Salmo trutta - 10 d

- 5 ma/l

Bioconcentration factor (BCF): 2.3

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

No data available

### 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

### **Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

### Contaminated packaging

Dispose of as unused product.

### 14. TRANSPORT INFORMATION

DOT (US)

UN number: 1690 Class: 6.1 Packing group: III

Proper shipping name: Sodium fluoride, solid

Reportable Quantity (RQ): 1000 lbs

Poison Inhalation Hazard: No

**IMDG** 

UN number: 1690 Class: 6.1 Packing group: III EMS-No: F-A, S-A

Proper shipping name: SODIUM FLUORIDE, SOLID

IATA

UN number: 1690 Class: 6.1 Packing group: III

Proper shipping name: Sodium fluoride, solid

## 15. REGULATORY INFORMATION

## **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

# **Massachusetts Right To Know Components**

Sodium fluoride CAS-No. Revision Date 2007-03-01

## **Pennsylvania Right To Know Components**

Sigma - S6776 Page 8 of 9

Sodium fluoride CAS-No. Revision Date 2007-03-01

**New Jersey Right To Know Components** 

Sodium fluoride CAS-No. Revision Date 2007-03-01

## California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### 16. OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Acute toxicity

Eye Irrit. Eye irritation
H300 Fatal if swallowed.
H301 Toxic if swallowed.
H315 Causes skin irritation.

H319 Causes serious eye irritation.

H402 Harmful to aquatic life.

## **HMIS Rating**

Health hazard: 4
Chronic Health Hazard: \*
Flammability: 0
Physical Hazard 0

# **NFPA** Rating

Health hazard: 3
Fire Hazard: 0
Reactivity Hazard: 0

### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

## **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.15 Revision Date: 06/02/2016 Print Date: 02/17/2018

Sigma - S6776 Page 9 of 9