

The ServiceMaster Company
One ServiceMaster Way
Downers Grove, IL 60515

MATERIAL SAFETY DATA SHEET

(Complies with 29 CFR 1910.1200)

1/800/333-6678

FiberFresh OD (Quick Dri)

Page 1 of 1

SECTION I

Product (Trade) Name: FiberFresh OD (Quick Dri)
 Manufacturer's Name: The ServiceMaster Company
 Address: One ServiceMaster Way, Downers Grove, IL 60515
 Emergency Telephone No: 1/800/333-6678
 Chemical Name and Synonyms: N/A
 Chemical Family: N/A
 Formula: N/A
 DOT Hazard Class: Flammable Liquid,
 N.O.S. (Isopropyl Alcohol)
 ID Number: UN 1993

SECTION II -- HAZARDOUS INGREDIENTS

Ingredient	C.A.S. No.	Wt. by %	OSHA		ACGIH		Listed As Carcinogenic By IARC, NTP
			PEL	TLV-TWA	STEL	OSHA, ACGIH	
Isopropyl alcohol	67-63-0	85.90	1000ppm	400 ppm	500 ppm	No	
Ethyl alcohol	64-17-5	1.5	1000ppm	1000ppm	N/E	No	

In accordance with OSHA's Hazard Communication Standard, ingredients listed in this section are those identified as being hazardous and present at concentrations greater than 1%, or greater 0.1% if the substance is a listed carcinogen. Information concerning ingredients identified as "Proprietary" will be made available as provided in 29 CFR 1910.1200(f).

SECTION III -- PHYSICAL DATA

Boiling Point (F): 180-185
 Vapor Pressure (mm hg): N/D
 Vapor Density (Air = 1): > 1
 Solubility in Water: Complete
 Appearance and Odor: Clear blue liquid with lemon fragrance.

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point (Tag, Closed Tester): 58°F
 Flammable Limits: LEL JEL 2 12.7
 Extinguishing Media: CO₂, dry chemical, alcohol-type foam, water fog.
 Special Fire Fighting Procedures: Self-contained breathing apparatus and protective clothing should always be worn in fighting fires involving chemicals.
 Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation and be ignited by heat, pilot lights, other flames or ignition sources at locations distant from material handling point.

SECTION V -- HEALTH HAZARD DATA

Primary Route(s) of Exposure: Inhalation.
 Threshold Limit Value: N/D for mixture. See Section II for TLV's of hazardous ingredients.
 Effects of Overexposure:
 - Acute: By Inhalation: Irritation of the nose and throat, dizziness, headaches, nausea, drowsiness, loss of consciousness.
 By Eye Contact: Irritation on contact with liquid or high concentrations of vapor.
 By Ingestion: Gastrointestinal irritation, nausea, vomiting, depression, respiratory difficulties, alcohol-like intoxication.
 By Skin Contact: Dryness, irritation, dermatitis.
 - Chronic: Prolonged or repeated breathing of vapors may cause irritation of nose and throat. Possible kidney effects. Prolonged or repeated skin contact may cause dryness, irritation, dermatitis.
 - Medical Conditions Generally Aggravated by Exposure: Pre-existing skin or respiratory disorders.

Emergency and First Aid Procedures:
 For Inhalation: Move to fresh air. Give artificial respiration if breathing has stopped and get medical attention.
 For Eye Contact: Flush with water for at least 15 minutes, lifting upper and lower lids occasionally. If irritation persists, call a physician.
 For Ingestion: Give several glasses of milk or water and induce vomiting. Call a physician.
 For Skin Contact: Remove any contaminated clothing. Immediately flush affected area with water for at least 15 minutes.

SECTION VI -- REACTIVITY DATA

Stability: Stable.
 Conditions to Avoid: None known.
 Incompatibility (Materials to Avoid): Contact with strong oxidizing agents, bleaches, aluminum.
 Hazardous Decomposition Products: On combustion or exposure to equivalent temperatures, carbon monoxide, carbon dioxide, organic acids, and other unidentified products of combustion.
 Hazardous Polymerization: Will not occur.

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled: Eliminate sources of sparks or flame. Ventilate the area. Wash away small amounts with water or add absorbent and remove with shovel.
 Waste Disposal Method: Place waste product or absorbed material in tightly sealed containers. Dispose of as ignitable, hazardous waste. Small amounts may be allowed to evaporate out of doors.
 Hazardous Waste Classification: D001

SECTION VIII -- SPECIAL PROTECTION INFORMATION

For Handling Product as Supplied:
 Respiratory Protection: If exposure exceeds TLV, use a NIOSH-approved respirator with a cartridge for organic vapors.
 Ventilation: Use with sufficient ventilation to maintain exposure below TLV.
 Eye Protection: NBR or rubber.
 Other Protective Equipment: If splashing occurs when handling, wear impervious apron and/or clothing as required to avoid skin contact.

For Handling Product After Dilution For Use:

Respiratory Protection: If exposure exceeds TLV, use a NIOSH-approved respirator with a cartridge for organic vapors.
 Ventilation: Use with sufficient ventilation to maintain exposure below TLV.
 Eye Protection: Not normally needed.
 Other Protective Equipment: Not normally needed.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Do not leave container open. Follow procedures for storage of flammable liquids. Keep away from heat, sparks, and fire.
 Other Precautions: Empty container may be hazardous. Rinse container before disposal.

Prepared By: Kevin T. Wagner
 Title: Occupational Safety and Health Coordinator

Date Prepared: November 13, 1996
 Supersedes previous form dated: October 3, 1995