

1. Identification

Product identifier GOLD MEDALIST WOOD GYM FINISH

Other means of identification

SDS number 550N-71A

Product code HIL00285

Recommended use Gym Finish

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name

HILLYARD INDUSTRIES

Address

302 North Fourth St.
St. Joseph, MO 64501

Contact person

Regulatory Affairs

Telephone number

(816) 233-1321 (Ext. 8285)

Fax

(816) 383-8485

E-mail

regulatoryaffairs@hillyard.com

Emergency telephone #

(800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure, or accident involving chemicals.)

2. Hazard(s) identification

Physical hazards

Flammable liquids

Category 3

Health hazards

Acute toxicity, inhalation

Category 4

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 2B

Sensitization, skin

Category 1

Germ cell mutagenicity

Category 1B

Carcinogenicity

Category 1B

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Specific target organ toxicity, repeated exposure

Category 1

Environmental hazards

Not classified.

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

NOTICE: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building.

NOTICE: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Use With Adequate Ventilation. Avoid breathing vapors or spray mist. Open windows and doors, use exhaust fans or other means to insure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Keep container closed when not in use. Do not take internally. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Stoddard Solvent		8052-41-3	50 - < 60
Xylene		1330-20-7	1 - < 3
Ethyl Benzene		100-41-4	< 1
Other components below reportable levels			40 - < 50

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth thoroughly. If swallowed, seek medical advice immediately and show this container or label.

Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	PEL	435 mg/m3
Stoddard Solvent (CAS 8052-41-3)	PEL	100 ppm 2900 mg/m3
Xylene (CAS 1330-20-7)	PEL	500 ppm 435 mg/m3 100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm 435 mg/m3 100 ppm
Stoddard Solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3
	TWA	350 mg/m3

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethyl Benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical splash goggles where there is a potential for eye contact.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing and gloves.

Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Clear, amber liquid
Physical state	Liquid.
Form	Liquid.
Color	Amber
Odor	Solvent odor
Odor threshold	Not available
pH	Not applicable
Melting point/freezing point	Not applicable / Not available
Initial boiling point and boiling range	> 300 °F (> 148.89 °C)
Flash point	> 100.0 °F (> 37.8 °C) Setaflash
Evaporation rate	< 1 Ethyl ether = 1
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2 hPa estimated 2.8 mm Hg
Vapor density	4.8 AIR=1
Relative density	0.872 at 77°F
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	7.26 lb/gal
Percent volatile	58 - 60 %
VOC (Weight %)	520 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	Harmful if inhaled. Narcotic effects. May cause an allergic skin reaction.
-----------------------	--

Product	Species	Test Results
GOLD MEDALIST WOOD GYM FINISH		

Acute

Dermal

LD50	Rabbit	3270.957 g/kg estimated
------	--------	-------------------------

Oral

LD50	Guinea pig	1261.8297 g/kg
	Mouse	67021.6328 mg/kg estimated
		1261.8297 g/kg
	Rabbit	336.4879 g/kg
	Rat	5000 mg/kg
		5 g/kg

Components	Species	Test Results
------------	---------	--------------

Ethyl Benzene (CAS 100-41-4)

Acute

Dermal

LD50	Rabbit	17800 mg/kg
------	--------	-------------

Oral

LD50	Rat	3500 mg/kg
------	-----	------------

Xylene (CAS 1330-20-7)

Acute

Dermal

LD50	Rabbit	> 43 g/kg
------	--------	-----------

Inhalation

LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours

Oral

LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
----------------------------------	-------------------------

Serious eye damage/eye irritation	Causes eye irritation.
--	------------------------

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
----------------------------------	-------------------------------

Skin sensitization	May cause an allergic skin reaction.
---------------------------	--------------------------------------

Germ cell mutagenicity	May cause genetic defects.
-------------------------------	----------------------------

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethyl Benzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species		Test Results
GOLD MEDALIST WOOD GYM FINISH			
Aquatic			
Crustacea	EC50	Daphnia	490.3439 mg/l, 48 hours estimated
Fish	LC50	Fish	1044.7705 mg/l, 96 hours estimated
Components	Species		Test Results
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Stoddard Solvent

3.16 - 7.15

Xylene

3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

Not Regulated For Ground Transportation.

General information

This material is regulated under IATA and IMDG regulations. Contact manufacturer for shipping instructions.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethyl Benzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Xylene	1330-20-7	1 - < 3

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethyl Benzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. Massachusetts RTK - Substance List

Ethyl Benzene (CAS 100-41-4)
Stoddard Solvent (CAS 8052-41-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Ethyl Benzene (CAS 100-41-4)
Stoddard Solvent (CAS 8052-41-3)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl Benzene (CAS 100-41-4)
Stoddard Solvent (CAS 8052-41-3)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Ethyl Benzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004
------------------------------	-----------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-10-2015

Version # 01

HMIS® ratings Health: 2*
Flammability: 3
Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.