

The ServiceMaster Company
One ServiceMaster Way
Downers Grove, IL 60515

SECTION I

Product (Trade) Name: FiberFresh GSL - Citrus
 Manufacturer's Name: The ServiceMaster Company
 Address: One ServiceMaster Way; Downers Grove, IL 60515
 Emergency Telephone No: 1/800/333-6678
 Chemical Name and Synonyms: N/A
 Chemical Family: N/A
 Formula: N/A
 DOT Hazard Class: Flammable Liquid, n.o.s.(1-methoxy, 2-propanol)
 DOT ID Number: UN1993

SECTION II -- HAZARDOUS INGREDIENTS

Ingredient	C.A.S.No.	Wt. by %	OSHA PEL		TLV-TWA ACGIH	Other Limit STEL	Listed As Carcinogenic BY IARC, NTP OSHA, ACGIH
			PEL	N/E			
d-Limonene	5989-27-5	50-60	N/E	N/E	N/E	N/E	No
Dipropylene glycol methyl ether	25265-71-8	20-30	100ppm	100ppm	150ppm	150ppm	No
Propylene glycol butyl ether	5131-66-8	20-30	N/E	N/E	N/E	N/E	No
Alcohol ethoxylate	68131-39-5	1-5	N/E	N/E	N/E	N/E	No

In accordance with OSHA's Hazard Communication Standard, ingredients listed in this section are those identified as being hazardous and present at concentrations greater than 1%, or greater than 0.1% if the substance is a listed carcinogen. Information concerning ingredients identified as "Proprietary" will be made available as provided in 29 CFR 1910.1200(h).

SECTION III -- PHYSICAL DATA

Boiling Point (°F): 338 - 448°
 Vapor Pressure (mm hg): 2 at 20°F
 Vapor Density (Air = 1): N/A
 pH: N/A
 Appearance and Odor: Colorless liquid with citrus/solvent odor

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point (Tag, Closed Tester): 124°F
 Flammable Limits: LEL UEL
 N/A N/A
 Extinguishing Media: Dry Chemical, CO₂
 Special Fire Fighting Procedures: Use a water spray to cool area. Fight fire from a safe distance, as pressure within closed containers can cause explosion. Use CO₂ or dry foam to extinguish fire, as floating solvents may spread.
 Unusual Fire and Explosion Hazards: Contents, when heated under pressure can be explosive. Aerosolized vapors may be heavier than air, and may run along the ground. When subjected to excessive heat or a spark, these vapors may explode.

SECTION V -- HEALTH HAZARD DATA

Primary Route(s) of Exposure: Skin contact.
 Threshold Limit Value: N/D for mixture. See Section II for TLV's hazardous ingredients
 Effects of Overexposure:
 - Acute: By Inhalation - May be irritating to the respiratory tract and mucous membranes. Possible headache, dizziness, and other CNS effects.
 By Eye Contact - May cause irritation, tearing, redness and/or swelling.
 By Ingestion - Small amounts aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema.
 By Skin Contact - Prolonged contact may result in irritation. Exposure to large amounts may produce anesthetic or narcotic effect.
 - Chronic: None known.
 - Medical Conditions Generally Aggravated by Exposure: Prolonged or repeated skin contact may aggravate some pre-existing skin disorders.

Emergency and First Aid Procedures:

For Inhalation - Immediately remove to fresh air. If irritation persists, get medical attention.
 For Eye Contact - Immediately rinse with cool water for at least 20 minutes. Hold eyelids apart to ensure flushing of entire surface. Get medical attention.
 For Ingestion - Do not induce vomiting. Give 2 large glasses of water and get medical attention.
 For Skin Contact - Remove contaminated clothing and launder before reuse. Wash skin thoroughly with a mild soap and water solution. Flush area with lukewarm water for 15 minutes. If irritation persists, get medical attention.

SECTION VI -- REACTIVITY DATA

Stability: Stable
 Conditions to Avoid: Heat, sparks, open flame, strong oxidizing conditions.
 Incompatibility (Materials to Avoid): Strong oxidizing agents, halogens, molten sulfur, extended contact with air or oxygen.
 Hazardous Decomposition Products: Combustion can produce carbon monoxide and perhaps other toxic gases.
 Hazardous Polymerization: Will not occur.

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material is Released Or Spilled: Eliminate all sources of ignition. Dike spill area and add absorbent. Containize for disposal.
 Waste Disposal Method: Consign away to licensed hazardous waste disposal company, as an ignitable hazardous waste.
 Hazardous Waste Classification: D001 - Ignitable

SECTION VIII -- SPECIAL PROTECTION INFORMATION

For Handling Product as Supplied:
 Respiratory Protection - Not normally required.
 Ventilation - Normal ventilation is adequate.
 Protective Gloves - Wear nitrile-coated or rubber gloves.
 Eye Protection - If splashing or misting may occur, wear chemical splash goggles.
 Other Protective Equipment - If splashing may occur, wear impervious apron and/or clothing as needed to prevent skin contact.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Store in cool, dry location. Keep away from heat, sparks, and open flame. Keep container closed.
 Other Precautions: Vapors of this product are heavier than air and will collect in low areas. Avoid exposure to sources of ignition. Empty containers may be hazardous.

Prepared By: Barry B. Ellegant
 Title: Product Development Chemist
 Approved By: Kevin T. Wagner
 Title: Occupational Safety and Health Coordinator

Date of Preparation: October 1, 1996
 Supersedes Previous Date: August 1, 1996